 AIR LIQUIDE	(Material Safety Data Sheet)	Doc.No.	MSDS-C-002
		Rev.No.	0
		Date	Apr.15.2005
(Carbon dioxide, Refrigerated)		Pages	2 /6

: ,
 :
 :
 : ,
 :
 :
 :
 : 가 가
 :

(OSHA):
 (NTP):
 (IARC):


4.

: , . 가
 : , 가 (105-115 F; 41-46
 C) 가 ,
 : 15
 : ,
 :

5.

:
 :
 : 가
 :
 : 0.8Km (1/2).

6.

	(Material Safety Data Sheet)	Doc.No.	MSDS-C-002
		Rev.No.	0
		Date	Apr.15.2005
(Carbon dioxide, Refrigerated)		Pages	3 / 6

가

7.

8.

(CARBON DIOXIDE, REFRIGERATED)

(CARBON DIOXIDE):

- TWA : 5000ppm, 9000mg/m3

- STEL : 30000ppm, 54000mg/m3

5000 ppm (9000 mg/m3) OSHA TWA

10000 ppm (18000 mg/m3) OSHA TWA (1993 6 30 58 FR 35338

)

30000 ppm (54000 mg/m3) OSHA STEL (1993 6 30 58 FR 35338

)

5000 ppm ACGIH TWA

30000 ppm ACGIH STEL

5000 ppm (9000 mg/m3) NIOSH TWA 10

30000 ppm (54000 mg/m3) NIOSH STEL

9100 mg/m3 (5000 ml/m3) DFG MAK (peak limitation category-IV)

가

:

가

()

: 가

: 가

:

,

:


:

(" ")

(NIOSH) /

(OSHA)

40,000 ppm

	(Material Safety Data Sheet)	Doc.No.	MSDS-C-002
		Rev.No.	0
		Date	Apr.15.2005
(Carbon dioxide, Refrigerated)		Pages	5 / 6

(CARBON DIOXIDE, REFRIGERATED)

:
 :
 가 :
 : 가

12.

:
 : 150000 ug/L 48 ()

13.

14.

U.S. DOT 49 CFR 172.101:

:
 ,

ID : UN 2187


: 2.2

: 2.2

15.

(CARBON DIOXIDE, REFRIGERATED)

:
 - :
 - :
 - :
 :
 CERCLA 103 (40CFR302.4):
 SARA 302 (40CFR355.30):
 SARA 304 (40CFR355.40):
 SARA , SARA 311/312 (40CFR370.21):
 :
 :
 :
 :

 AIR LIQUIDE	(Material Safety Data Sheet)	Doc.No.	MSDS-C-002
		Rev.No.	0
		Date	Apr.15.2005
(Carbon dioxide, Refrigerated)		Pages	6 / 6

SARA 313 (40CFR372.65):

OSHA (29CFR1910.119):

:

65 (): .

:

(EC) :

가 :

(TSCA):

TSCA 12(b) :

16.

가

가

()

/ 가

(Compatibility)

MSDS

(European Directives)

가

AIR LIQUIDE S.A.

MSDS ALK